

IN THE CLAIMS

1. (Currently Amended) A computerized method of reconstructing media data from higher moment data, the method comprising:

performing a finite Radon transform on the higher moment data;

generating an average function to allow inversion of the Radon transform in one step;

correlating the Radon transform output at each point;

calculating a resultant set of duplications using the correlation process to generate a new average function;

summing partial backprojections of the Radon transform at each point; and

subtracting the new average function for each point from the sum of the partial backprojections at that point, wherein the subtracting reconstructs the media data.

2. (Original) The method of claim 1 wherein performing the Radon transform results in data selected from the group consisting of three dimensional data, two dimensional data, and n-dimensional data where n is greater than three.

3. (Original) The method of claim 1 wherein the average function is calculated based on geometry and used for multiple reconstructions.

4. (Currently Amended) The method of claim 1 wherein the method of reconstructing data from higher moment data ~~including the step of~~ further comprises backprojecting a constant function to allow ~~allows~~ geometries with no closed form to be trained.

5. (Currently Amended) A system for reconstructing media data from higher moment data, the system comprising:

means for performing a finite Radon transform on the higher moment data;

means for generating an average function to allow inversion of the Radon transform in one step;

means for correlating the Radon transform output at each point;

means for calculating a resultant set of duplications using the correlation process to generate a new average function;

means for summing partial backprojections of the Radon transform at each point; and

means for subtracting the new average function for each point from the sum of the partial backprojections at that point, wherein the means for subtracting reconstructs the media data.

Alt
CDL-1

6. (Currently Amended) A computer readable medium comprising instructions, which when executed on a processor, perform a method of reconstructing media data from higher moment data, the method comprising:

performing a finite Radon transform on the higher moment data;

generating an average function to allow inversion of the Radon transform in one step;

correlating the Radon transform output at each point;

calculating a resultant set of duplications using the correlation process to generate a new average function;

summing partial backprojections of the Radon transform at each point; and

subtracting the new average function for each point from the sum of the partial backprojections at that point, wherein the subtracting reconstructs the media data.

7. (Currently Amended) An apparatus for reconstructing media data from higher moment data, the apparatus comprising:

a Radon transform module to perform a finite Radon transform on the higher moment data;

an average function generator to generate an average function to allow inversion of the Radon transform in one step, the average function generator coupled to the Radon transform module;

a correlation module to correlate the Radon transform output at each point, the correlation module coupled to the Radon transform ~~transform~~ module;

a calculator to calculate a resultant set of duplications using the correlation process and to generate a new average function, the calculator coupled to the correlation module;

a summing module to sum partial backprojections of the Radon transform at each point, the summing module coupled to the Radon transform module; and

Alp
con's a subtracting module to subtract the new average function for each point from the sum of the partial backprojections at that point, the subtracting module coupled to the summing module and the calculator, wherein the subtracting module reconstructs the media data.

8. (Original) The apparatus of claim 7 wherein the Radon transform module outputs data selected from the group consisting of three dimensional data, two dimensional data, and n-dimensional data where n is greater than three.

9. (Original) The apparatus of claim 7 wherein the average function is calculated based on geometry and used for multiple reconstructions.

10. (Original) The apparatus of claim 7 wherein a plurality of geometries with no closed form are trained using the apparatus for reconstructing data from higher moment data by backprojecting a constant function.

11. (New) The method of claim 1, wherein the media data is selected from the group consisting of audio data, video data and image data.

12. (New) The system of claim 5, wherein the media data is selected from the group consisting of audio data, video data and image data.

Alp
COPY 13. (New) The computer readable medium of claim 6, wherein the media data is selected from the group consisting of audio data, video data and image data.

14. (New) The apparatus of claim 7, wherein the media data is selected from the group consisting of audio data, video data and image data.
